according to Regulation (EC) No 1907/2006

Revision date: 15.04.2021

Product code: 2222

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond Total Etch (bond A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH		
Street:	Elbgaustraße 248		
Place:	D-22547 Hamburg		
Telephone:	+49. (0) 40. 84006-0	Telefax:+49. (0) 40. 84006-222	
e-mail:	info@dmg-dental.com		
Internet:	www.dmg-dental.com		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1 Hazard Statements: May cause respiratory irritation. Causes serious eye damage. May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H335	May cause respiratory irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

Precautionary statements

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 2 of 5

Hazardous components

CAS No	Chemical name		Quantity
	EC No Index No REACH No		
	Classification (Regulation (EC) No 1272/2008)		
1565-94-2	Bis-GMA		15 - 25 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
1565-94-2		Bis-GMA	15 - 25 %
	oral: LD50 = 50	00 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 3 of 5

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid yellow	
Odour:	like: ester	
Changes in the physical state		
Boiling point or initial boiling point and boiling range:		100 °C
point of decomposition:		> 200 °C
Flash point:		> 100 °C
pH-Value (at 20 °C):		4.5 - 7
Solubility in other solvents Solubility ca. 50 %		
Vapour pressure: (at 20 °C)		23 hPa
Density:		1,1 g/cm³
Relative vapour density:		> 1

SECTION 10: Stability and reactivity

according to Regulation (EC) No 1907/2006

Revision date: 15.04.2021

Product code: 2222

Page 4 of 5

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

LD50: Rat 5500mg/kg

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1565-94-2	Bis-GMA					
	oral	LD50 mg/kg	5000	Rat	literature value	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation. Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Aquatoxicity LC50: > 360 mg / I / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of harzardous waste according to official regulations.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021

Product code: 2222

Page 5 of 5

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D):

- - non-hazardous to water

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond Total Etch Bond B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supp	lier of the safety data sheet	
Company name:	DMG Chemisch-Pharmazeutische F	abrik GmbH
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax:+49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1 Hazard Statements: May cause respiratory irritation. Causes serious eye damage. May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H335	May cause respiratory irritation.	
H318	Causes serious eye damage.	
H317	May cause an allergic skin reaction.	
acutionany atatamanta		

Precautionary statements

P333+P313 P305+P351+P338	If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 2 of 5

Hazardous components

CAS No	Chemical name						
	EC No	EC No Index No REACH No					
	Classification according to Regulation (EC) No. 1272/2008 [CLP]						
1565-94-2	Bis-GMA						
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335						

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

SECTION 8: Exposure controls/personal protection

according to Regulation (EC) No 1907/2006

	LuxaBond Total Etch Bond B	D 0 (5
Revision date: 14.04.2016	Product code: 2222	Page 3 of 5
8.1. Control parameters		
8.2. Exposure controls		
Appropriate engineering controls Ensure adequate ventilation of the s	torage area.	
Protective and hygiene measures When using do not eat or drink.		
Eye/face protection Tightly sealed safety glasses.		
Hand protection Tested protective gloves are to be w Respiratory protection	rorn: Suitable material: NBR (Nitrile rubber).	
The following must be prevented: in	halation.	
SECTION 9: Physical and chemical p	roperties	
9.1. Information on basic physical and ch	emical properties	

Physical state: Colour:	liquid yellow	
Odour:	like: ester	
pH-Value (at 20 °C):		4.5 - 7
Changes in the physical state		
Initial boiling point and boiling range:		100 °C
point of decomposition:		> 200 °C
Flash point:		> 100 °C
Vapour pressure: (at 20 °C)		23 hPa
Density:		1,1 g/cm³
Solubility in other solvents Solubility ca. 50 %		
Vapour density:		> 1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016

Product code: 2222

Page 4 of 5

Acute toxicity

LD50: Rat 5500mg/kg

CAS No	Chemical name								
	Exposure route Dose Species Source Method								
1565-94-2	Bis-GMA								
	oral	LD50 mg/kg	5000	Rat	literature value				

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Aquatoxicity LC50: > 360 mg / I / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

180106

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of harzardous waste according to official regulations .

Waste disposal number of waste from residues/unused products

WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D):

- not water contaminating

SECTION 16: Other information

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B							
Revision date: 14.04.2016	Product code: 2222	Page 5 of 5					
Relevant H and EUH statements (number and full text)							
H315	Causes skin irritation.						
H317	May cause an allergic skin reaction.						
H318	Causes serious eye damage.						
H319	Causes serious eye irritation.						
H335	May cause respiratory irritation.						

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

according to Regulation (EC) No 1907/2006

	LuxaBond Total Etch	_Pre-bond	
evision date: 15.04.2021	Product code: 6	\$700	Page 1 of
ECTION 1: Identification of	the substance/mixture and of the c	ompany/undertaking	
.1. Product identifier			
LuxaBond Total Etch_Pre	-bond		
CAS No:	64-17-5		
Index No:	603-002-00-5		
EC No:	200-578-6		
.2. Relevant identified uses of	the substance or mixture and uses adv	rised against	
Uses advised against			
pregnant or breastfeeding	people should not work with hazardous	substances	
.3. Details of the supplier of th	<u>e safety data sheet</u>		
Company name:	DMG Chemisch-Pharmazeutisch	e Fabrik GmbH	
Street:	Elbgaustraße 248		
Place:	D-22547 Hamburg		
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-22	22
e-mail:	info@dmg-dental.com		
Internet:	www.dmg-dental.com		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name					
	EC No	EC No Index No REACH No					
	Classification (Regulation (EC) No 1272/2008)						
64-17-5	ethanol; ethyl alcohol	ethanol; ethyl alcohol					
	200-578-6	603-002-00-5					
	Flam. Liq. 2; H225						

Full text of H and EUH statements: see section 16.

Specific Conc	Specific Conc. Limits, M-factors and ATE						
CAS No	CAS No EC No Chemical name						
	Specific Conc. Limits, M-factors and ATE						
64-17-5	17-5 200-578-6 ethanol; ethyl alcohol						
	inhalation: LC50 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg						

SECTION 4: First aid measures

4.1. Description of first aid measures

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 2 of 6

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Change contaminated clothing. Rub greasy ointment into the skin.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

If swallowed, immediately drink: Water. Medical treatment necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Atomized water. alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Concentrated vapors are heavier than air. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. The following must be prevented: inhalation. skin contact. Eye contact.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep away from sources of ignition - No smoking. Provide adequate ventilation.

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 3 of 6

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

8.2. Exposure controls



Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation. exceeding exposure limit values: Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid colourless-transparent
Odour:	characteristic
Melting point/freezing point:	ca115 °C
Boiling point or initial boiling point and boiling range:	ca. 80 °C
Lower explosion limits:	3.5 vol. %
Upper explosion limits:	15 vol. %
Flash point:	The product has not been tested.
Auto-ignition temperature:	425 °C
pH-Value:	neutral
Water solubility:	complete miscible
Vapour pressure:	59 hPa
(at 20 °C)	
Density (at 20 °C):	ca. 0,8 g/cm³
Viscosity / dynamic:	1,3 mPa·s
(at 20 °C)	

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat.

10.5. Incompatible materials

Oxidizing agents. peroxides. acid. Alkali metals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute toxicity, oral LD50: (Rat): > 10000 mg/kg

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond

Revision date: 15.04.2021

Product code: 6700

Page 4 of 6

CAS No	Chemical name									
	Exposure route	Exposure route Dose Species Source Method								
64-17-5	ethanol; ethyl alcohol	ethanol; ethyl alcohol								
	oral	LD50 mg/kg	6200	Rat	IUCLID					
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS					

Irritation and corrosivity

In case of prolonged or frequently repeated skin contact: irritant.; Following eye contact: irritant.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity (Leuciscus idus): LC50: > 8140 mg / 1 / 48 h (Ethanol); Acute Daphnia toxicity (Daphnia magna): EC50: 9268 - 14221 mg / 1 / 48 h

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method	
64-17-5	ethanol; ethyl alcohol					
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h Daphnia magna	IUCLID		

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64-17-5	ethanol; ethyl alcohol					
	Biologische Abbaubarkeit	94 %		OECD 301E		
	leicht biologisch abbaubar					
	Chemischer Sauerstoffbedarf	930-1670 mg/g	5			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No Chemical name		Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Remove according to the regulations.

List of Wastes Code - residues/unused products

according to Regulation (EC) No 1907/2006

Revision date: 15	.04.2021	LuxaBond Total Etch_Pre-bond Product code: 6700	Page 5 of 6		
180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste					
SECTION 14: T	ransport information				
14.2. UN prop	ber or ID number: her shipping name: ht hazard class(es):	UN 1170 ETHANOL (ETHYL ALCOHOL) 3 II 3			
Classification Special Provis Limited quanti Transport cate Hazard No: Tunnel restrict Other applica E2	sions: ty: egory:	F1 144 601 1 L 2 33 D/E port)			
Marine transport <u>14.1. UN num</u> <u>14.2. UN prop</u>	ber or ID number: per shipping name: ort hazard class(es): I group:	UN 1170 ETHANOL (ETHYL ALCOHOL) 3 II 3			
Special Provis Limited quant EmS: Other applica E2		144 3 L F-E, S-D ansport)			
<u>14.1. UN num</u> 14.2. UN prop	AO-TI/IATA-DGR) <u>ber or ID number:</u> <u>er shipping name:</u> <u>rt hazard class(es):</u> <u>group:</u>	UN 1170 ETHANOL (ETHYL ALCOHOL) 3 II 3			
IATA-packing IATA-max. qu	sions: ty Passenger: instructions - Passenger: antity - Passenger: instructions - Cargo:	A3 1 L 353 5 L 364			

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch_Pre-bond							
Revision date: 15.04.2021	Product code: 6700	Page 6 of 6					
IATA-max. quantity - Cargo: Other applicable information (air transpor E2 : Y341	60 L *t)						
14.5. Environmental hazards							
ENVIRONMENTALLY HAZARDOUS:	No						
SECTION 15: Regulatory information							
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture						
EU regulatory information							
Restrictions on use (REACH, annex XVII): Entry 3, Entry 40							
National regulatory information							
Water hazard class (D):	1 - slightly hazardous to water						
SECTION 16: Other information							
·							
Delevent II and EIIII statements (number							

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
EUH210	Safety data sheet available on request.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DMG Etching Gel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Chemisch-Pharmazeutische I	DMG Chemisch-Pharmazeutische Fabrik GmbH				
Street:	Elbgaustraße 248					
Place:	D-22547 Hamburg					
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222				
e-mail:	info@dmg-dental.com					
Internet:	www.dmg-dental.com					

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Corr. 1B; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

phosphoric acid; orthophosphoric acid 100 %

Signal word:

Pictograms:



Danger

Hazard statements

H314

Causes severe skin burns and eye damage.

Precautionary statements

P280	Wear protective gloves and eye/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization PHOSPHORIC ACID

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7664-38-2	phosphoric acid; orthophosphoric acid 100 %			35 - < 40 %
	231-633-2	015-011-00-6	01-2119485924-24	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1B; H290 H302 H314			

Full text of H and EUH statements: see section 16.

Specific Co	Specific Conc. Limits, M-factors and ATE					
CAS No	EC No	Chemical name	Quantity			
	Specific Conc. Limits, M-factors and ATE					
7664-38-2	231-633-2	phosphoric acid; orthophosphoric acid 100 %	35 - < 40 %			
		250 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 19: >= 10 - < 25				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 3 of 9

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. The product itself does not burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Wear suitable protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Ensure adequate ventilation of the storage area.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

Hints on joint storage

Do not store together with: Alkalis (alkalis). metal.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	
		-	2		STEL (15 min)	

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 4 of 9

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7664-38-2 phosphoric acid; orthophosphoric acid 100 %						
Worker DNEL,	acute	inhalation	local	2 mg/m³		
Worker DNEL, long-term		inhalation	local	1 mg/m³		
Consumer DNE	EL, long-term	inhalation	local	0,73 mg/m³		

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable gloves.: NBR (Nitrile rubber). Butyl rubber.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. exceeding exposure limit values: Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Jelly	
Colour:	blue	
Melting point/freezing point:		not determined
Boiling point or initial boiling point ar	nd	100 °C
boiling range:		
Flammability:		not determined
Lower explosion limits:		not applicable
Upper explosion limits:		not determined
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:		not determined
pH-Value:		1
Water solubility:		easily soluble.
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined

according to Regulation (EC) No 1907/2006

DMG Etching Gel		
Revision date: 23.09.2022	Product code: 020223	Page 5 of 9
Vapour pressure: (at 23 °C)	20 hPa	
Density:	1,4 g/cm³	
Relative vapour density:	< 1	
9.2. Other information		
Information with regard to physical haza	rd classes	
Explosive properties		
The product is not: Explosive.		
Oxidizing properties		
The product is not: oxidising.		
Other safety characteristics		
Evaporation rate:	not determined	
Solid content:	not determined	

SECTION 10: Stability and reactivity

10.1. Reactivity

Possibility of hazardous reactions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Alkalis (alkalis).

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

LD50: Rat >810mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-38-2	phosphoric acid; orthophosphoric acid 100 %				
		LD50 1250 mg/kg	Rat	supplier SDS	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Irritant effect on the eye: Causes burns.

After skin contact: Causes burns.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 6 of 9

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met. The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7664-38-2	phosphoric acid; orthophosphoric acid 100 %						
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus	SDS	OECD 201
	Acute crustacea toxicity	EC50 mg/l	> 100		Daphnia magna (Big water flea)	SDS	OECD 202
	Acute bacteria toxicity	(EC50 mg/l)	>1000	3 h	Activated sludge	ECHA	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

according to Regulation (EC) No 1907/2006

	· ·	
	DMG Etching Gel	
Revision date: 23.09.2022	Product code: 020223	Page 7 of 9
(EXCEPT KITCHEN AND CARE); wastes from natal	OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH care, diagnosis, treatment or prevention of disease in humans; containing hazardous substances; hazardous waste	
Contaminated packaging		
Non-contaminated packages may be r	ecycled. Handle contaminated packages in the same way as the	
substance itself.		
SECTION 14: Transport information		
Land transport (ADR/RID)		
Land transport (ADR/RID) <u>14.1. UN number or ID number:</u>	UN 1805	
14.2. UN proper shipping name:	PHOSPHORIC ACID, SOLUTION	
14.3. Transport hazard class(es):	8	
14.4. Packing group:		
Hazard label:	8	
	Â.	
	8	
Classification code:	C1 Č	
Limited quantity:	5 L	
Excepted quantity:	E1	
Transport category:	3	
Hazard No:	80	
Tunnel restriction code:	E	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1805	
14.2. UN proper shipping name:	PHOSPHORIC ACID, SOLUTION	
14.3. Transport hazard class(es):	8	
<u>14.4. Packing group:</u> Hazard label:	 8	
Special Provisions:	223	
Limited quantity:	5 L	
EmS:	F-A, S-B	
Other applicable information (marine tra E1	insport)	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1805	
14.2. UN proper shipping name:	PHOSPHORIC ACID, SOLUTION	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
Hazard label:	8	
Special Provisions:	A3	
Limited quantity Passenger:	1L	
IATA-packing instructions - Passenger:	852	
IATA-max. quantity - Passenger:	5 L	

according to Regulation (EC) No 1907/2006

	DMG Etching Col	
Revision date: 23.09.2022	DMG Etching Gel Product code: 020223	Page 8 of 9
IATA-packing instructions - Cargo:	856	1 490 0 01 0
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	60 L	
Other applicable information (air transpo		
E1		
: Y841		
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: strongly corrosive.		
14.7. Maritime transport in bulk according to	IMO instruments	
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulation	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII):		
Entry 75		
2004/42/EC (VOC):	0,5 % (7 g/l)	
Information according to 2012/18/EU	Not subject to 2012/18/EU (SEVESO III)	
(SEVESO III):		
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the	
	'juvenile work protection guideline' (94/33/EC).	
Water hazard class (D):	2 - obviously hazardous to water	
15.2. Chemical safety assessment		
Chemical safety assessments for subst	ances in this mixture were not carried out.	
SECTION 16: Other information		
Abbreviations and acronyms		
CLP: Classification, labelling and Packa	iging	
REACH: Registration, Evaluation and A	uthorization of Chemicals	
	Classification, Labelling and Packaging of Chemicals	
UN: United Nations		
CAS: Chemical Abstracts Service DNEL: Derived No Effect Level		
DMEL: Derived Minimal Effect Level		
PNEC: Predicted No Effect Concentrati	on	
ATE: Acute toxicity estimate		
LC50: Lethal concentration, 50%		
LD50: Lethal dose, 50%		
LL50: Lethal loading, 50%		
EL50: Effect loading, 50% EC50: Effective Concentration 50%		
ErC50: Effective Concentration 50%, gr	owth rate	
NOEC: No Observed Effect Concentrat		
BCF: Bio-concentration factor		
PBT: persistent, bioaccumulative, toxic		
vPvB: very persistent, very bioaccumula		
ADK: Accord europeen sur le transport	des marchandises dangereuses par Route	

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

according to Regulation (EC) No 1907/2006

DMG Etching Gel

Revision date: 23.09.2022

Product code: 020223

Page 9 of 9

RID: Regulations concerning the international carriage of dangerous goods by rail IMDG: International Maritime Code for Dangerous Goods EmS: Emergency Schedules MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Internediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern For abbreviations and acconvms. see: ECHA Guidance on information requirements and che

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure	
Skin Corr. 1B; H314	Calculation method	
Eye Dam. 1; H318	Calculation method	

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)