

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
Trade name: Signum universal bond II
 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 Application of the substance / the mixture Dental bonding material
• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Kulzer GmbH Leipziger Straße 2, 63450 Hanau (Germany) Tel.: +49 (0)800 4372522
• Informing department: E-Mail: msds@kulzer-dental.com • 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463
SECTION 2: Hazards identification
- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms GHS02 GHS07 GHS09
· Signal word Danger
-
 Hazard-determining components of labelling: methyl methacrylate
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide tert-butyl perbenzoate
 Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
· Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment.
P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

(Contd. of page 1)

Trade name: Signum universal bond II

- · 2.3 Other hazards -
 - Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.

3.2 Mixtures • Description: Product based (on methacrylates	
 Dangerous components: 		
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-75%
CAS: 72869-86-4 EINECS: 276-957-5 Reg.nr.: 01-2120751202-68-xxxx	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	25-50%
CAS: 75980-60-8 EINECS: 278-355-8 Reg.nr.: 01-2119972295-29-xxxx	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2, H361f Aquatic Chronic 2, H411 Skin Sens. 1B, H317	≥2.5-<3%
CAS: 614-45-9 EINECS: 210-382-2	tert-butyl perbenzoate Org. Perox. C, H242 Aquatic Acute 1, H400 Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<i>≥</i> 0.1-<0.25%

SECTION 4: First aid measures

- 4.1 Description of first aid measures
 - After inhalation Supply fresh air; consult doctor in case of symptoms. • After skin contact
 - Instantly wash with water and soap and rinse thoroughly.
 - If skin irritation continues, consult a doctor.
 - After eye contact
 - Rinse opened eye for several minutes under running water. Then consult doctor.
 - After swallowing
 - Rinse out mouth and then drink plenty of water.
 - In case of persistent symptoms consult doctor.
 - Product based on methacrylates
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

(Contd. of page 2)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water. • For safety reasons unsuitable extinguishing agents Water.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.
 - · Additional information -

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
- 6.4 Reference to other sections
- No dangerous materials are released.
- See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

 7.1 Precautions for safe handling Keep containers tightly sealed.
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities • Storage

- Requirements to be met by storerooms and containers:
- Dry place, storage temperature <25 ° C
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store container in a well ventilated position.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

- WEL Short-term value: 416 mg/m³, 100 ppm
 - Long-term value: 208 mg/m³, 50 ppm

· DNELs

80-62-6 methyl methacrylate

Oral	general population, long term, systemic	8.2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.67 mg/Kg/d (not defined)
	general population, long term, systemic	8.2 mg/Kg/d (not defined)

(Contd. on page 4)

GB -



Page 4/11

- GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

-	worker industrial, acute, l	ocal	416 mg/m3 (not defined)
	worker industrial, long tei		348.4 mg/m3 (not defined)
I	worker industrial, long ter	•	208 mg/m3 (not defined)
	general population, acute		208 mg/m3 (not defined)
	• • •	,	74.3 mg/m3 (not defined)
	• • • •	•	-3,14-dioxa-5,12-diazahexadecane-1,16-di
Oral	general population, long	term. svstemic	0.3 ma/Ka (not defined)
Dermal	worker industrial, long ter	-	1.3 mg/Kg/d (not defined)
	÷	•	0.7 mg/Kg/d (not defined)
Inhalative	worker industrial, long ter	-	3.3 mg/m3 (not defined)
	general population, long	-	
75980-60-	8 diphenyl(2,4,6-trimeth	-	
Oral		• • • •	0.0833 mg/Kg (not defined)
Dermal	worker industrial, long ter	-	0.233 mg/Kg/d (not defined)
	_		0.0833 mg/Kg/d (not defined)
Inhalative	worker industrial, long ter	-	0.822 mg/m3 (not defined)
	general population, long	term, systemic	0.145 mg/m3 (not defined)
· PNE	ECs		
80-62-6 m	ethyl methacrylate		
freshwater		0.94 mg/l (not	,
marine water		0.094 mg/l (no	,
sewage treatment plant		10 mg/l (not de	
	dry weight, freshwater	10.2 mg/Kg (n	·
		0.102 mg/Kg (l	
soil, dry we	-	1.48 mg/Kg (n	
72869-86-	4 7,7,9(or 7,9,9)-trimetl bismethacrylate	hyl-4,13-dioxo	o-3,14-dioxa-5,12-diazahexadecane-1,16-di
freshwater	-	0.01 mg/l (not	defined)
marine wa	ter	0.001 mg/l (no	t defined)
sewage tre	eatment plant	3.61 mg/l (not	defined)
sediment,	dry weight, freshwater	4.56 mg/Kg (n	ot defined)
sediment,	dry weight, marine water	0.46 mg/Kg (n	ot defined)
soil, dry we	-	0.91 mg/Kg (n	
75980-60-	8 diphenyl(2,4,6-trimeth		
freshwater		0.0014 mg/l (n	·
marine wa		0.00014 mg/l (
	dry weight, freshwater	0.115 mg/Kg (i	,
		0.0115 mg/Kg	. ,
soil, dry we	•	0.0222 mg/Kg	. ,
· Ada	litional information: The	lists that were	valid during the compilation were used as basis
	ure controls priate engineering contr	ols No further	data; see item 7. (Contd. on pag



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

 Individual protection measures, such as protection 	(Contd. of page 4
	personal protective equipment
General protective and hygienic meas	
Keep away from foodstuffs, beverages ar	
Instantly remove any soiled and impregna	ated garments.
Wash hands during breaks and at the end	d of the work.
Avoid contact with the eyes and skin.	
· Breathing equipment:	
Not neccessary with efficient local exhau	ist. If exposition to vapours is possible, use breathing
protective mask (filter A).	
Hand protection	
	ble and resistant to the product/ the substance/ the
preparation.	1
	eration of the penetration times, rates of diffusion and
the degradation	, , ,
If skin contact cannot be avoided, pro-	tective gloves are recommended to avoid possible
sensitization.	
Solvent resistant gloves	
Check protective gloves prior to each use	o for their proper condition
· Material of gloves	
The selection of the suitable gloves	does not only depend on the material, but also or
further merks of quality and varian fro	om manufacturer to manufacturer. As the product is a
number marks of quality and valles no	the registered of the glove meterial can not be
preparation of several substances	, the resistance of the glove material can not be
	ore to be checked prior to the application.
Penetration time of glove material	
	be found out by the manufacturer of the protective
gloves and has to be observed.	
 For the permanent contact of a may 	ximum of 15 minutes gloves made of the following
· ····································	
materials are suitable:	
materiaİs are suitable: Butyl rubber, BR	
materiaİs are suitable: Butyl rubber, BR Nitrile rubber, NBR	
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses	
materiaİs are suitable: Butyl rubber, BR Nitrile rubber, NBR	
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective	e clothing
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p	e clothing properties
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi	e clothing properties
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information	e clothing properties ical properties
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state	e clothing properties ical properties Fluid
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour:	e clothing properties ical properties Fluid Colourless
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell:	e clothing properties ical properties Fluid Colourless Ester-like
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold:	e clothing properties ical properties Fluid Colourless Ester-like Not determined.
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point: • Boiling point or initial boiling point and boiling range	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point: • Boiling point or initial boiling point and boiling range • Flammability	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point: • Boiling point or initial boiling point and boiling range • Flammability	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C
<i>materials are suitable:</i> Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point: • Boiling point or initial boiling point and boiling range	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable.
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol %
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol % 10 °C (80-62-6 methyl methacrylate)
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR • Eye/face protection Safety glasses • Body protection: Light weight protective SECTION 9: Physical and chemical p • 9.1 Information on basic physical and chemi • General Information • Physical state • Colour: • Smell: • Odour threshold: • Melting point/freezing point: • Boiling point or initial boiling point and boiling range • Flammability • Lower and upper explosion limit • Lower: • Upper: • Flash point: • Ignition temperature:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol % 10 °C (80-62-6 methyl methacrylate) 430.0 °C
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Ignition temperature:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol % 10 °C (80-62-6 methyl methacrylate)
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Ignition temperature: Decomposition temperature:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol % 10 °C (80-62-6 methyl methacrylate) 430.0 °C Not determined.
materials are suitable: Butyl rubber, BR Nitrile rubber, NBR Eye/face protection Safety glasses Body protection: Light weight protective SECTION 9: Physical and chemical p 9.1 Information on basic physical and chemi General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Ignition temperature:	e clothing properties ical properties Fluid Colourless Ester-like Not determined. Not determined d 100 °C Not applicable. 2.1 Vol % 12.5 Vol % 10 °C (80-62-6 methyl methacrylate) 430.0 °C



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

	(Contd. of page S
Viscosity:	
 Kinematic viscosity 	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
 Partition coefficient n-octanol/water (log 	1
value)	Not determined.
· Steam pressure at 20 °C:	47 hPa
 Density and/or relative density 	
· Density at 20 °C	1.000 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
	further relevant information available.
Appearance: Form:	Fluid
· Important information on protection of	
health and environment, and on safety.	Due duet is uset as linuities
Self-inflammability:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
• • • • • • • • • • • • • • • • • • •	explosive air/vapour mixtures is possible.
Change in condition	
· Evaporation rate	Not determined.
 Information with regard to physical hazard 	
classes	
· Explosives	Void
· Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	
Highly flammable liquid and vapour.	
Flammable solids	Void
• Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
• Self-heating substances and mixtures	Void
[•] Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void
Desensuiseu explosives	VOIU

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
 10.2 Chemical stability
 Conditions to be avoided: No decomposition if used and stored according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known **10.4 Conditions to avoid** No further relevant information available.

• **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)

GB



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

(Contd. of page 6)

Trade name: Signum universal bond II

• 10.6 Hazardous decomposition products: None Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

	-	sed on available data, the classification criteria are not met.
		es that are relevant for classification:
	ethyl meth	•
Oral	LD50	~7,900 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
		29.8 mg/l (rat)
72869-86-	bismetha	•
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
75980-60-		l(2,4,6-trimethylbenzoyl)phosphine oxide
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	LD50	>2,000 mg/kg (rat) (OECD 402)
		perbenzoate
Oral	LD0	2,000 mg/kg (rat) (OECD 423)
Dermal	LD0	2,000 mg/kg (rat) (OECD 402)
Inhalative		1.01 mg/L (rat) (OECD 439)
		4.9 mg/L (rat) (OECD 439)
	orrosion/ir	
Seriou Respir May ca	atory or sl use an alle	age/irritation Based on available data, the classification criteria are not met. kin sensitisation ergic skin reaction. enicity Based on available data, the classification criteria are not met.
· Carcin · Reproc · STOT-s May ca	ogenicity luctive tox single exp use respira	Based on available data, the classification criteria are not met. cicity Based on available data, the classification criteria are not met. osure atory irritation.
• Aspira 11.2 Infor	tion hazar mation on	xposure Based on available data, the classification criteria are not met. d Based on available data, the classification criteria are not met. other hazards
· ENGOC	nne aisrup	oting properties ots is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

80-62-6 methyl methacrylate

EC50/21d 49 mg/L (daphnia) (OECD 211)

(Contd. on page 8)

GB



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

		(Contd. of page 7)
EC50		69 mg/l (daphnia) (EPA OTS 797.1300)
		37 mg/l (daphnia) (OECD 211)
ErC50	0 / 72 h	>110 mg/l (algae) (OECD 201)
NOE	C / 72h	110 mg/l (algae) (OECD 201)
NOE	C / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC5	50 / 72h	>110 mg/l (algae) (OECD 201)
NOE	C/ 35d	9.4 mg/L (fish) (OECD 210)
	/ 35d	33.7 mg/L (fish) (OECD 210)
72869		,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl
		pismethacrylate
EC50		>1.2 mg/l (daphnia) (OECD 202)
LC50,		10.1 mg/l (fish) (OECD 203)
		>0.68 mg/l (algae) (OECD 201)
		0.21 mg/l (algae) (OECD 201)
		liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
EC50)/48h	10,100 mg/l (algae)
		3.53 mg/l (daphnia) (OECD 202)
LC50,		1.4 mg/l (fish) (OECD 203)
		>2.01 mg/l (algae) (OECD 201)
ErC10	0/72h	1.56 mg/L (algae) (OECD 201)
		ence and degradability
		hyl methacrylate
		on 94 % /14d (not defined) (OECD 301C)
	b	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate
Biode	egradatio	on 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
7598(0-60-8 a	liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Biode	egradatio	on 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)
		Imulative potential
		liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
		tion factor (BCF) 47-55 (not defined)
12.5 PE VF 12.6	Results BT: Not PvB: No Endocri	r in soil No further relevant information available. of PBT and vPvB assessment applicable. t applicable. ine disrupting properties on on endocrine disrupting properties see section 11.
· 12.7 (Other a	dverse effects No further relevant information available.
SEC	TION	13: Disposal considerations
· 13.1	Waste t	reatment methods

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

(Contd. on page 9)

ĠВ



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022


(Contd. of page 8)

Trade name: Signum universal bond II

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.





Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

	(Contd. of page S
 Kemler Number: EMS Number: Stowage Category Stowage Code 	33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
 14.7 Maritime transport in bulk according IMO instruments 	to Not applicable.
· Transport/Additional information:	-
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	1L Code: E2 Maximum net quantity per inner packaging 30 ml Maximum net quantity per outer packaging 500 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging 30 ml Maximum net quantity per outer packaging 500 ml
· UN "Model Regulation":	UN1247, METHYL METHACRYLATI MONOMER, STABILIZED, solution, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Relevant phrases

- H225 Highly flammable liquid and vapour.
- Heating may cause a fire. Causes skin irritation. H242

H315

- H317 May cause an allergic skin reaction.
- Harmful if inhaled. H332
- May cause respiratory irritation. H335
- Suspected of damaging fertility. H361f
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11) GB



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2022

Version number 1

Revision: 27.10.2022

Trade name: Signum universal bond II

(Contd. of page 1	10)
H412 Harmful to aquatic life with long lasting effects.	, i
EUH204 Contains isocyanates. May produce an allergic reaction.	
· Abbreviations and acronyms:	
SADT: Self Accelerating Decomposition Temperature	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreeme	ent
Concerning the International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
DNEL: Derived No-Effect Level (UK REACH)	
PNEC: Predicted No-Effect Concentration (UK REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2 Ora, Barry, C: Organia paravidae, Tuna C/D	
Org. Perox. C: Organic peroxides – Type C/D Acute Tox. 4: Acute toxicity – Category 4	
Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Skin Find. 2. Skin consistent mation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Active 1: hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* * Data compared to the previous version altered.	
Data compared to the previous version altered.	0.5
	- GB